



| Model | PT7E122S200 | PT7E120S400 |
|---------------------------|---|---|
| Camera | | |
| Image Sensor | 1/2.9" SONY Low Illumination 2.4MP CMOS Sensor | 1/3" OV High-resolution 4.0MP CMOS Sensor |
| Horizontal Resolution | 1080P | 4MP |
| S/N Ratio | >50db | >50db |
| PTZ | | |
| Horizontal Rotation Speed | 120°/S | |
| Horizontal Rotation Range | 360° | |
| Tilt Rotation Speed | 60°/S | |
| Tilt Rotation Range | 93° | |
| Auto Flip | Support | |
| Ratio Speed | Support | |
| 360° Scan | Support | |
| A-B Scan | Support | |
| Preset Points | 220 | |
| Guard Tours | 3 groups | |
| Guard Points | Max.16 points | |
| Lens | | |
| Focus Length | 3.9mm-85.5mm | 4.7mm-94mm |
| Focus Control | 22X Optical Zoom | 20X Optical Zoom |
| Night Vision | | |
| Infrared LED | Φ 42x8PCS | |
| IR Range | 120m | |
| Auto Control IR LED | PWM | |
| Network | | |
| Network protocol | TCP/IP , TTP , NTP , IGMP , DHCP , UDP , SMTP , RTP , RTSP , ARP , DDNS , DNS , PPPoE , P2P | |
| ONVIF | Support | |
| Network interface | Built-in RJ45 network interface,support 10M/100M IP DATA | |
| General | | |
| Weatherproof | IP66 | |
| Operating Temperature | Indoor: 0°~ +40° Outdoor: -20°~ +60° | |
| Operating Humidity | ≤90% Non Condensing | |
| Heater & Blower | Auto temperature control | |
| Power | DC12V/4A | |
| Lightning Protection | Transient voltage 6000V | |
| Dimension | 31x31x44(cm) | |
| Weight | 8.3Kgs | |