

DHI-NVR4216-I

16Channel 1U WizSense Network Video Recorder



Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

System Overview

Dahua new NVR4000-I network video recorder delivers excellent performance and high recording quality that is ideally suitable for IP video surveillance applications. This NVR adopts powerful processor, providing the capability of 4K resolution processing for applications where image details are highly required. Besides, the NVR supports input, recording and transmission functions. Additionally, the NVR can be served as edge storage, central storage or backup storage with an intuitive shortcut operation menu for remote management and control.

With build-in deep learning module, NVR4000-I series products adopt video image structuring technology based on deep learning algorithms, achieving high-precision human face recognition and perimeter protection. By applying deep learning artificial intelligence, NVR4000-I allows users to focus on what matters most, improves event response time and helps make video actionable.

The NVR is compatible with numerous third-party devices, which make it the perfect solution for surveillance systems that work independently of video management system (VMS).

Functions

Perimeter Protection

Automatically filtering out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improving alarm accuracy.

Real Time Face Recognition

Video stream & picture stream real time face recognition. Facial attributes analysis features including gender, age, expression, glasses, moustache, mouth mask. Identify people and also capture, record faces with metadata. Facial feature filtering while real time display, only show faces with target features.

- 16 Channel IP video access
- Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- Up to 4 Channel perimeter protection
- Up to 2 Channel video stream face recognition/8 channel picture stream face recognition (with FD camera)
- Up to 12 face pictures/sec processing
- \cdot Up to 10 face databases with 20,000 face images in total



Face Database Management

Configurable multiple face databases. Powerful face database management. Face database can be applied to video channels independently. Name, gender, birthday, address, certificate type, certificate No., countries®ions and state can be added to each face picture.

Common/Stranger Mode

NVR4000-I supports common and stranger mode. In stranger mode, when NVR detects a strange face (not in device's face database), it can trigger alarm, buzzer, snapshot, record, etc. Similarity threshold can be set manually. This function is developed for important infrastructure sites for which access control is critical.

AI Search

Support seach by metadata of human and vehicles. Support uploading face pictures to NVR and compare them with recorded faces in NVR by similarity. Enable operators to quickly and easily search through multi channels and long duration, efficiently find out when and where a person of interest appeard.

ANPR

Automatic Number Plate Recognition available for convenient entrance/ exit management. Support license plate recognition (working with Dahua ITC camera), black/white list import/export, add/delete B/W list number, search result from recorded video.



Wiz Sense | DHI-NVR4216-I

Technical Specification

recinical specification			
System			
Main Processor	Multi-core embedded processor		
Operating System	Embedded LINUX		
Perimeter Protection			
Performance	4 channel, 10 IVS rules for each channel		
Object classification	Human/Vehicle secondary recognition for tripwire and intrusion		
Al Search	Search by target classification (Human, Vehicle)		
Face Recognition			
Performance	Max 12 face pictures/sec processing		
	2 channel video stream face recognition/8 channel picture stream face recognition (with FD camera)		
Stranger Mode	Detect strangers' faces (not in device's face database). Similarity threshold can be set manually.		
AI Search	Up to 8 target face images search at same time, similarity threshold can be set for each target face image.		
Database Management	Up to 10 face databases with 20,000 face images in total. Name, gender, birthday, address, certificate type, certificate No., countries®ions and state can be added to each face picture.		
Database Application	Each database can be applied to video channels independently.		
Trigger Events	Buzzer, Voice Prompts, Email, Snapshot, Recording, Alarm Out, PTZ Activation, etc.		
Audio and Video			
IP Camera Input	16 Channel		
Two-way Talk	1 Channel Input, 1 Channel Output, RCA		
Display			
Interface	1 HDMI, 1 VGA		
Resolution	HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720		
Decoding Capability	2-ch@8MP (30fps), 8-ch@1080P (30fps)		
Multi-screen Display	1/4/8/9/16		
Recording			
Bandwidth	200 Mbps (80 Mbps when Al function enabled, based on Dahua private protocol)		
Compression	Smart H.265+/H.265/Smart H.264+/H.264/MJPEG		
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1 etc.		
Record Mode	Manual, Schedule (Continuous, MD (Motion Detection), Alarm, IVS)		
Record Interval	1–120 min (default: 60 min), Pre-record: 1–30 sec, Post- record: 10–300 sec		
Video Detection and Alarm			
Trigger Events	Alarm Out, Video Push, Email, Recording, PTZ, Tour, Snapshot, Voice Prompt, Buzzer and Screen Tips		
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Scene Change		
Alarm Input	4 Channel		

Alarm Output	2 Channel		
Playback and Backup			
Sync Playback	1/4/9/16		
Search Mode	Time/Date, Alarm, MD and Exact Search (accurate to second)		
Backup Mode	USB Device/Network		
Third-party Support			
Third-party Support	Arecont Vision, Airlive, AXIS, Canon, Dynacolor, JVC, LG, Panasonic, Pelco, Xunmei, Samsung, Sanyo, Sony, Watchnet and more		
Network			
Interface	1 RJ-45 Port (10/100/1000 Mbps)		
PoE	NA		
Network Function	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE,DDNS, FTP, Alarm Center, IP Search (Support Dahua IP camera, DVR, NVS, etc.), P2P		
Max. User Access	128 users		
Mobile App	iPhone, iPad, Android		
Interoperability	ONVIF (Profile S), SDK, CGI		
Storage			
Internal HDD	2 SATA III Ports, Up to 8 TB capacity for each HDD		
eSATA	NA		
Auxiliary Interface			
USB	2 USB Ports (1 Rear USB 2.0 , 1 Front USB 2.0)		
RS232	NA		
RS485	NA		
Electrical			
Power Supply	Single, DC 12V, 4A		
Power Consumption	NVR: <2.9W (Without HDD)		
Environmental			
Operating Conditions	-10°C to +55°C (+14°F to +131°F), 86–106kpa		
Storage Conditions	0°C to +40°C (+32°F to +104°F), 30–85% RH		
Construction			
Dimensions	1U, 375.0 mm × 282.4 mm × 56.0 mm (14.76" × 11.12" × 2.20")		
Net Weight	1.55 kg (3.4 lb) (without HDD)		
Gross Weight	2.81 kg (6.2 lb) (without HDD)		
Certifications			
CE	EN55035, EN55032, EN55024, EN50130-4, EN60950-1		
FCC	Part 15 Subpart B, ANSI C63.4-2014		
UL	UL 60950-1		

Wiz Sense | DHI-NVR4216-I

Ordering Information

Туре	Model	Description
16 Channel WizSense NVR	DHI-NVR4216-I	16 Channel 1U WizSense Network Video Recorder

Dimensions (mm[inch])



