

DS-PDD12P-EG2-WE Wireless Dual-Tech Detector

DS-PDD12P-EG2-WE is a fully supervised two-way wireless detector featuring motion and microwave detection, tamper protection, low battery and supervision. It can operate for up to 5 years from two in-built batteies, and monitors the area within 12m radius, ingnores animals while recognizing human from the first step.



- 3D optics including creep-zone protection, full coverage without dead angle
- 24G microwave to prevent wall penetration
- Digital temperature compensation
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Easy replaceable battery with PCB protected
- Frequency hopping against jamming for reliable transmission





Specification

Detection Performance		
Detection Method	Passive Infrared, Microwave	
Sensor Model	SFG321-711	
Detection Range	12m	
Detection Angle	85.9°	
Detection Zones	52	
Detectable Speed	0.3 to 2m/s	
Sensitivity	Auto,High,Pet	
Pet Immunity	30Kg	
White Light Filter	6500lux	
Microwave Frequency	24GHz(24.15 ~ 24.25GHz)	
Digital Temperature Compensation	Support	
Creep Zone Protection	Support	
Feature		
Digital Processing	Support	
Sealed Optics	Support	
Tamper Protection	Front,Rear	
Environment Temperature		
Indicator	Support	
Signal Strength Indicator	Support	
Interface		
Power Switch	Power Up Enrolling	
LED Indicator	Green(PIR), Red(Microwave), Blue(Alarm)	
Transmission		
Transmission Technology	Tri-X Wireless	
Transmission Method	Two-Way RF Wireless	
Transmission Frequency	868MHz	
Transmission Security	AES-128 Encryption	
Transmission Range(Free Space)	1.6Km	
Frequency Hopping	Support	
Enrolling Method	Power up,Remote ID,QR Code	
Electrical Characteristics		
Standard Battery Life	5 years in work status (being triggered 20 times per day)	
Power Supply	Battery Powered	
Battery Type	CR123A × 2	
Typical Voltage	3V	
General		
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)	
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)	
Operation Humidity	10% to 90%	



Weight	141g
Mounting Height	1.8 to 2.4m
Mounting Method	Wall
Application Scenario	Indoor
Bracket	Optional Wall & Driving Accessory

Available Model

DS-PDD12P-EG2-WE

Accessory

Optional

DS-PDB-IN-Wallbracket Internal ceiling mounted bracket	DS-PDB-IN-Ceilingbracket Internal wall mounted bracket	DS-PDP-IN-CR123A Indoor Detector Battery
0		Littlian Battery LMANO, + CR123A 3.0V -



Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com **Hikvision Russia** T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com